

## Deep Bass Wireless Headphones with Bass Reactor RB-M500BE

## General

Driver Unit (mm)	40 mm (1-9/16 in.)		
Magnet Type	Neodymium		
Impedance ( $\Omega$ ) (Power off, with cord)	27 Ω		
Sensitivity (dB/mW) (Power off, with cord)	100 dB / mW		
Frequency Information	Frequency Response (with cord)	20 Hz – 20000 Hz	
	Frequency Band (with Bluetooth®)	20 Hz - 20000 Hz	
Control/ Mic	•/•		
Playback Time with Battery	Approx. 30 hours ( Bass reactor: Off, SBC)		
Charging Time (25°C/ 77°F)	Approx. 4 hours		
Quick Charge (15 minutes)	Approx. 2 hours		
Weight (without cord)	Approx. 316 g (11.1 oz)		
Supplied Item	USB charging cord: Approx. 0.5 m (1.6 ft.)  * Input Plug: USB A Shape, Output Plug: USB Type-C Shape Detachable cord: Approx. 1.2 m (3.9 ft.)		
Cord	Cord Length (m)	1.2 m (3.9 ft.) detachable	
	MiniPlug (3.5 mm)	•	
	Plug	Gold	
Advanced Function			
Bluetooth® Wireless Technology	Version	5.0	

Specs - RB-M500BE Overhead Wireless & Stereo Headphones - Panasonic UK & Ireland				
	Supported Profiles	A2DP, AVRCP, HSP, HFP		
	Codec	SBC, AAC		
	Operating Distance	Up to 10 m (33 ft.)		
Active Noise Cancelling	-			
Bass Reactor	•			
NOTE				
Specifications are subject to change without notice. All numbers given here are approximate.				
FRADEMARK NOTICE				

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Panasonic Corporation is

Consumer > Home Entertainment > Headphones and Earphones > Overhead Wireless & Stereo Headphones > RB-M500BE > All Specs

under license. Other trademarks and trade names are those of their respective owners.