

## Deep Bass Wireless Headphones with Bass Reactor RB-M500BE

## General

Driver Unit (mm)	40 mm (1-9/16 in.)		
Magnet Type	Neodymium		
Impedance ( $\Omega$ ) (Power off, with cord)	27 Ω		
Sensitivity (dB/mW) (Power off, with cord)	100 dB / mW		
Frequency Information	Frequency Response (with cord)	20 Hz – 20000 Hz	
	Frequency Band (with Bluetooth®)	20 Hz - 20000 Hz	
Control/ Mic	•/•		
Playback Time with Battery	Approx. 30 hours ( Bass reactor: Off, SBC)		
Charging Time (25°C/ 77°F)	Approx. 4 hours		
Quick Charge (15 minutes)	Approx. 2 hours		
Weight (without cord)	Approx. 316 g (11.1 oz)		
Supplied Item	USB charging cord: Approx. 0.5 m (1.6 ft.)  * Input Plug: USB A Shape, Output Plug: USB Type-C Shape Detachable cord: Approx. 1.2 m (3.9 ft.)		
Cord	Cord Length (m)	1.2 m (3.9 ft.) detachable	
	MiniPlug (3.5 mm)	•	
	Plug	Gold	
Advanced Function			

	Supported Profiles	A2DP, AVRCP, HSP, HFP	
	Codec	SBC, AAC	
	Operating Distance	Up to 10 m (33 ft.)	
Active Noise Cancelling	-		
Bass Reactor	•		
NOTE			
· Specifications are subject to change without notice. All numbers given here are approximate.			

## TRADEMARK NOTICE

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Panasonic Corporation is under license. Other trademarks and trade names are those of their respective owners.

 ${\tt Consumer} \ > \ {\tt Home\ Entertainment} \ > \ {\tt Headphones\ and\ Earphones} \ > \ {\tt Overhead\ Wireless\ \&\ Stereo\ Headphones} \ > \ {\tt RB-M500BE} \ > \ {\tt All\ Specs}$