



HP V27i 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black

Brand : HP

Product code: 95V94AA#ABB

Product name : V27i

- 68.6cm (27") Full HD 1920 x 1080 IPS
 - 5ms, 16:9, 300cd/m², 1000:1
 - USB, VGA, HDMI
- 68.6cm (27") Full HD 1920 x 1080 IPS, 16:9, 300cd/m², 5ms, 178°/178°, 1000:1

HP V27i 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black:

An everyday monitor that's easy on you.

Browse the web, stream your shows, and get some work done —all with plenty of room- on the extra-large HP V27i FHD Monitor that adjusts to your comfort needs and delivers stunning picture quality and expansive views in highly affordable style.

HP V27i. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	HDMI ports quantity	1
Display brightness (typical)	300 cd/m ²	HDMI version	1.4
Display resolution *	1920 x 1080 pixels	Audio input	✗
Native aspect ratio *	16:9	Headphone out *	✗
Response time	5 ms	HDCP	✓
HD type *	Full HD	Ergonomics	
Display technology *	LCD	Panel mounting interface	100 x 100 mm
Screen shape *	Flat	Cable lock slot *	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1440 x 900 (WXGA+), 1600 x 900, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)	VESA mounting *	✓
		Height adjustment *	✗
Contrast ratio (typical) *	1000:1	Pivot	✗
Maximum refresh rate *	60 Hz	Swivelling	✗
Viewing angle, horizontal	178°	Tilttable	✓
Viewing angle, vertical	178°	Tilt angle range	-5 - 20°
Panel type *	IPS	Power	
Pixel pitch	0.311 x 0.311 mm	Energy efficiency class (SDR) *	E
Pixel density	81 ppi	Energy consumption (SDR) per 1000 hours *	20 kWh
Horizontal scan range	30 - 80 kHz	Power consumption (typical) *	28 W
Vertical scan range	50 - 60 Hz	Power consumption (standby) *	0.5 W
RGB colour space	NTSC	AC input voltage	100 - 240 V
Colour gamut	72%	Operational conditions	
Performance		Operating temperature (T-T)	5 - 35 °C
HP segment	Home	Operating relative humidity (H-H)	20 - 80%
Multimedia		Sustainability	
Built-in speaker(s) *	✗	Sustainability certificates	CE, ENERGY STAR, TCO
Built-in camera *	✗	Weight & dimensions	
		Width (with stand)	612.2 mm
		Depth (with stand)	200.1 mm
		Height (with stand)	447.7 mm

Design		Weight & dimensions	
Market positioning *	Home	Width (without stand)	61.2 cm
Product colour *	Black	Depth (without stand)	4.77 cm
Country of origin	China	Height (without stand)	36.8 cm
Certification	Australian-New Zealand MEPS; BIS; BSMI; CB; CCC; CE; CECP; CEL; C-Tick; cTUVus; EAC; Energy Star; E-standby; EUP Lot-5; EUP Lot-6; FCC; ISO 9241-307; KC/KCC; NOM NYCE; PSB; SEPA; TCO Certified; TUV Bauart; VCCI; Vietnam MEPS; WEEE; ISC; Low blue light; UkrSEPRO; South Africa MEPS; Ukraine Energy label; California Energy Commission (CEC); WW application; ICE; Mexico MEPS; TGM; Japan PC Green Label	Weight (without stand)	4.5 kg
		Packaging data	
		Cables included	AC, HDMI
		Package width	675 mm
		Package depth	128 mm
		Package height	425 mm
		Package weight	5.7 kg
		Package type	Box
Ports & interfaces		Other features	
Built-in USB hub *	✓	Energy efficiency class (old)	A+
USB hub version	3.2 Gen 1 (3.1 Gen 1)		
USB Type-A downstream ports quantity	3		
VGA (D-Sub) ports quantity	1		
DVI port	✗		
HDMI *	✓		