

Philips V Line LCD monitor with SmartControl Lite 223V5LSB2/10

Brand : Philips

Product family: V Line

Product code: 223V5LSB2/10

Product name : LCD monitor with SmartControl Lite 223V5LSB2/10

- V Line
- 21.5" (54.6 cm)
V Line LCD monitor with SmartControl Lite

Philips V Line LCD monitor with SmartControl Lite 223V5LSB2/10:

Enjoy vivid LED pictures on this Philips display. Equipped with SmartControl lite, it's a great choice! Philips V Line LCD monitor with SmartControl Lite 223V5LSB2/10. Display diagonal: 54.6 cm (21.5"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED. Display: LED. Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 90°, Viewing angle, vertical: 65°. VESA mounting. Product colour: Black



Display		Ergonomics	
Display diagonal *	54.6 cm (21.5")	Cable lock slot type	Kensington
Display resolution *	1920 x 1080 pixels	Tilttable	✓
HD type *	Full HD	Tilt angle range	-5 - 20°
Native aspect ratio *	16:9	Picture-in-Picture	✗
Display technology *	LED	On Screen Display (OSD)	✓
Panel type *	TFT/S-PVA	On Screen Display (OSD) languages	Simplified Chinese, Czech, German, Dutch, English, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Turkish, Ukrainian
Backlight type	W-LED	Number of OSD languages	18
Touchscreen *	✗	Plug and Play	✓
Display brightness (typical)	200 cd/m ²	LED indicators	Operation, Stand-by
Response time	5 ms	Power	
Screen shape *	Flat	Energy efficiency class (SDR) *	E
Supported graphics resolutions	1920 x 1080 (HD 1080)	Energy consumption (SDR) per 1000 hours *	16 kWh
Aspect ratio	16:9	Power consumption (typical) *	15.61 W
Contrast ratio (typical) *	600:1	Power consumption (standby) *	0.5 W
Contrast ratio (dynamic)	10000000:1	Power consumption (off)	0.5 W
Viewing angle, horizontal	90°	AC input voltage	100 - 240 V
Viewing angle, vertical	65°	AC input frequency	50/60 Hz
Display number of colours *	16.78 million colours	Energy efficiency scale	A to G
Pixel pitch	0.248 x 0.248 mm	Operational conditions	
Horizontal scan range	30 - 83 kHz	Operating temperature (T-T)	0 - 40 °C
Vertical scan range	56 - 76 Hz	Storage temperature (T-T)	-20 - 60 °C
Viewable size, horizontal	47.7 cm	Operating relative humidity (H-H)	20 - 80%
Viewable size, vertical	26.8 cm	Operating altitude	0 - 3658 m
Digital horizontal frequency	30 - 83 kHz	Non-operating altitude	0 - 12192 m
Digital vertical frequency	56 - 76 Hz	Relative humidity	20 - 80%
Sync-on-green (SOG)	✓		
RGB colour space	sRGB		
3D	✗		
Separate H/V sync	✓		
Performance			
NVIDIA G-SYNC *	✗		

Performance		Packaging content	
Component video sync	Separate sync	Stand included	✓
Flicker-free technology	✓	Manual	✓
Windows operating systems supported	✓	Weight & dimensions	
Mac operating systems supported	✓	Width (with stand)	503 mm
Multimedia		Depth (with stand)	213 mm
Built-in speaker(s) *	✗	Height (with stand)	376 mm
Built-in camera *	✗	Weight (with stand)	2.61 kg
Design		Width (without stand)	50.3 cm
Market positioning *	Home	Depth (without stand)	5 cm
Product colour *	Black	Height (without stand)	31.6 cm
Feet colour	Black	Weight (without stand)	2.35 kg
Certification	BSMI, CE Mark, FCC Class B, GOST, PSB, SASO, SEMKO, TUV/ISO9241-307, cETLus, WEEE	Packaging data	
Compliance industry standards	BSMI, CE Mark, FCC Class B, GOST, PSB, SASO, SEMKO, TUV/ISO9241-307, cETLus, WEEE	Package width	555 mm
Ports & interfaces		Package depth	107 mm
Built-in USB hub *	✗	Package height	414 mm
VGA (D-Sub) ports quantity	1	Package weight	3.87 kg
DVI port	✗	Sustainability	
Audio input	✗	Sustainability certificates	EPEAT Silver, ENERGY STAR
Headphone out *	✗	Logistics data	
Network		Harmonized System (HS) code	85285210
Wi-Fi	✗	Thin Client	
Bluetooth	✗	Thin client installed	✗
Ethernet LAN	✗	Other features	
Ergonomics		Display	LED
VESA mounting *	✓	On/off switch	✓
Panel mounting interface	100 x 100 mm	Built-in subwoofer	✗
Cable lock slot *	✓	TV tuner integrated	✗
		Recommended resolution	1920 x 1080 @ 60 Hz
		Recyclable packaging material	100%
		Energy efficiency class (old)	E
		Mean time between failures (MTBF)	30000 h



8712581689568

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-NOV-2022. Prints or copies of Information are only valid on the printed Publication date